

### Piaggio Beverly 300 ie - Technical specifications

<b>Engine</b>	Piaggio single-cylinder 4-stroke
<b>Engine capacity</b>	278 cc
<b>Bore x stroke</b>	75 mm / 63 mm
<b>Power</b>	22.2 hp at 7,250 rpm
<b>Torque</b>	23 Nm at 5,750 rpm
<b>Timing system</b>	Single overhead camshaft (SOHC) - 4 valves
<b>Fuel system</b>	Electronic injection
<b>Cooling</b>	Liquid
<b>Lubrication</b>	Wet sump
<b>Starter</b>	Electric with oil-bath free wheel
<b>Transmission</b>	Twist-and-go CVT with torque server
<b>Clutch</b>	Automatic, centrifugal dry clutch
<b>Frame</b>	Double cradle in high strength tubular steel
<b>Front Suspension</b>	Telescopic hydraulic fork with 35-mm stanchions – wheel travel 90 mm
<b>Rear suspension</b>	Double hydraulic shock absorbers with adjustable preload with 4 settings – wheel travel 81 mm
<b>Front brake</b>	300-mm disc brake with two-piston floating calliper
<b>Rear brake</b>	240-mm disc brake with two-piston floating calliper
<b>Front wheel rim</b>	Aluminium alloy 16" x 3.00
<b>Rear wheel rim</b>	Aluminium alloy 14" x 3.50
<b>Front tyre</b>	Tubeless 110/70 - 16"
<b>Rear tyre</b>	Tubeless 140/70 - 14"
<b>Length/Width</b>	2,150 mm / 780 mm
<b>Wheelbase</b>	1,535 mm
<b>Seat height</b>	790 mm
<b>Fuel tank capacity</b>	12.5 litres
<b>Kerb weight</b>	165 Kg
<b>Emissions compliance</b>	EURO 3